

SAGEMCOM

FAX 4565 VERSATILE & COST SAVING

Laser Fax, Telephone, Copier and Direct USB**

Large 200 Page memory

30 sheets automatic document
feeder

convenient calling/redial list of 50
numbers

sophisticated 8 ringer melodies for
VIP function*

250 name/number entries with
quick search function

comfortable direct-USB functions

environmental friendly power &
toner save mode



FAX 4565

TECHNICAL SPECIFICATIONS

Laser Fax

ITU Group 3 compatible	T.30 standard
Fax Type	G3
Modem speed	14400bps
Error correction mode (ECM)	
Fast fax transmission	6 sec. / page
Scanning resolution	200 dpi
Printing resolution	600 dpi
Page memory	200
Automatic document feeder (ADF)	30 sheets
Paper tray	250 pages
Timer function	
Polling receive	
Secure fax reception via password	
Calling/redial list	50 numbers
Group dialling	249 records
Broadcasting	20 entries
Caller ID* (CLIP)	
Predefined fax forms	
Calendar function	
Time stamp function	
Real time clock (with back up for up to 48h)	

Telephone

Name/number entries with quick search function	250
Calling/redial list	50 numbers
On-hook dialling	
Caller ID*	
Ringer melodies for VIP function*	8

Printer

Printing speed	24 ppm
Printing resolution	600 x 1200 dpi
Single sheet bypass	

Copier

Multicopy	up to 99 pages
Zoom function	25 – 400 %
Copy resolution	up to 400 x 200 dpi
Grey scales	64
Customizable copy profiles	
Mosaic function (copy 2 or 4 pages on 1)	

Direct USB**

Print from USB stick (jpg, tiff, txt)	
Scan to USB stick (jpg, tiff, pdf)	
Archive incoming faxes on USB stick	

ECO FUNCTIONS

Toner save mode (up to 40%)	
Power save mode	
Mosaic function (copy 2 or 4 pages on 1)	

Logistical data

9 NC	288 138 5XX
Type number	FAX4565/XX
EAN Code	3425 16026 XXXX
Designed for	PSTN/PABX
Power supply	195 – 264V AC/47

POWER CONSUMPTION

Stand by	typ. < 4 W
Transmission	typ. < 15W
Reception	typ. < 15W
Print	typ. < 500 W
Copy	typ. < 500W

DISPLAY

Liquid crystal display, 16 characters/2lines, European characters

DIMENSIONS (W X D X H)

Unpacked	390 x 390 x 291
Packed	485 x 500 x 380

WEIGHT

Unpacked	8,8 kg
Packed	10 kg

TEMPERATURE RANGE

Operation	5 ~ 35° C
Storage packed	-25 ~ 50° C
Storage unpacked	0 ~ 40° C

RELATIVE HUMIDITY

Operation	15 ~ 85 % RH
Storage packed	5 ~ 95 % RH
Storage unpacked	15 ~ 85 % RH

STANDARD PACKAGE INCLUDES

Fax machine incl. cables	
Quick installation guide	
Document tray	
Starter Toner	

ACCESSORIES

SAGEMCOM CTR 356 toner cartridge and drum unit

* Depends on the availability of the service on the local operators network

** USB stick not included

SAGEMCOM

Sagem Communications Austria GmbH
Gutheil-Schoder-Gasse 17
1230 Wien / Austria
www.sagemcom.com